

Dialight




SafeSite® LED High Bay - High Efficiency - ATEX / IECEx

for Outdoor Industrial Applications

March 2018





Features & Benefits

- 10 year warranty
- L70 rated for >150,000 hours @ 25°C ambient
- Low power consumption
- Instant on/off
- Low Maintenance
- Mercury free
- No UV or IR
- Resistant to shock and vibration
- Superior colour rendition index compared to HPS, LPS, MV
- Optional glass retention film available

Application


The Dialight SafeSite[®] LED High Bay luminaire was designed specifically to replace conventional lighting in a wide variety of indoor & outdoor hazardous area applications. Its low profile light weight design and versatile mounting options make it ideal for High Bay applications for ATEX and IECEx classified hazardous area zones. Dialight's long life LED luminaires are designed to meet the most demanding specification criteria while offering maximum energy savings, reduced maintenance costs, and a superior quality of light.

SafeSite[®] LED High Bay - High Efficiency - ATEX / IECEx

Standard Models



Patent pending



Dimensions in mm (inches)

Certifications & Ratings (All Models)

- ATEX / IECEx Zones 1, 21
- ATEX / IECEx Zones 2, 22
- CE
- ABS Design Assessed: (pending)
- IP66
- RoHS compliant

Certifications & Ratings (IIB Models)

- Ex II 2 GD Ex d* IIB T4 Gb
- Ex tb IIIC 135°C
- Certificate numbers: Baseefa 10ATEX0148X IECEx BAS 10.0074X

*Add EX e for factory fitted junction box

Certifications & Ratings (IIB + H2 Models)

- Ex II 2 GD Ex d* IIB+H2 T4 Gb
- Ex tb IIIC 135°C
- Certificate numbers: Baseefa 12ATEX0070X IECEx BAS 12.0044X

*Add EX e for factory fitted junction box

Mechanical Information:

- Fixture weight:** 14.6 kg (31 lbs) with fixed cable
16.1 kg (34 lbs) with junction box
- Mounting:** Aluminium stirrup mounting bracket included
- Wiring options:** Factory installed 3 meter SWB cable or factory fitted junction terminal box with 2 off M20 x 1.5mm or 2 off M25 x 1.5mm cable entries

Electrical Specifications:

- Operating voltage:** 110 – 277V AC, 50/60Hz: 23,500lm models
100 – 277V AC, 50/60Hz: 16,000lm and lower models
- Total system power consumption:** See table
- Operating temperature:** -40°C to +60°C
- Harmonics:** IEC 61000-3-2
- Surge protection:** Protection devices capable of handling up to 6kV. Tested for 6kV/2 ohm combination wave, as per IEEE C62.41, line-line and line-ground
- THD:** <20%
- Power factor:** > 0.9

Construction:

- Housing:** Copper free aluminum
- Finish:** Superior dual coat finish
- Sealed polyester topcoat
- Chemical resistant epoxy primer
- Lens¹:** Tempered glass (optional fragment retention film available)

Photometric Information:

- CRI:** 75
- CCT:** 5000K (cool white)
4000K (neutral white)

All values typical unless otherwise stated (tolerance +/- 10%)

¹For information on chemical compatibility, please follow this link to reference Dialight's Chemical Compatibility Guide: www.dialight.com/pubs/MDTFCHEMRFLX001.PDF

SafeSite® LED High Bay - High Efficiency - ATEX / IECEx

Mounting Options and Accessories



HBXW3

- Aluminium swivel bracket (included with fixture)



HBXW3-SSL-304FT

- 304 stainless steel forward throw bracket

HBXW3-SSL-316FT

- 316 stainless steel forward throw bracket



HBXW3-SSL-316M

- 316 Stainless steel bracket

HBXW3-SSL-304M

- 304 Stainless steel bracket



HBXSBDK

- Sand blast kit (dome lens)

HBXSDL

- Sacrificial dome lens




HBXSBK

- Sand blast kit (flat lens)

HBXSBL


- Sacrificial flat lens

HBXW3 - Swivel Bracket Dimensions



Dimensions in mm

High Bay with Junction Box Dimensions




Dimensions in mm


SafeSite[®] LED High Bay - High Efficiency - ATEX / IECEx

Light Distribution Pattern


Medium Pattern



Wide Pattern



Narrow Pattern



SafeSite® LED High Bay - High Efficiency - ATEX / IECEx

Ordering Information - Standard models

Part Number	Hydrogen Environments	Initial Fixture Lumens	Typical Wattage	Maximum Wattage	Lm/W	IP Rating	Voltage	Colour Temperature (CCT)	Lens	Light Distribution
Standard Models										
HEA9MC4PN-BCG		23,500	212	235	110	IP66	110 - 277V AC	5000K (cool white)	Glass	Medium
HEA9RC4PN-BCG		23,500	212	235	110	IP66	110 - 277V AC	5000K (cool white)	Glass	Wide
HEA9NC4PN-BCG		23,500	212	235	110	IP66	110 - 277V AC	5000K (cool white)	Glass	Narrow
HEA9MC4KN-BCG		16,000	144	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Medium
HEA9RC4KN-BCG		16,000	144	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Wide
HEA9NC4KN-BCG		16,000	144	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Narrow
HEA9MC4GN-BCG		12,500	112	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Medium
HEA9RC4GN-BCG		12,500	112	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Wide
HEA9NC4GN-BCG		12,500	112	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Narrow
HEA9MC4DN-BCG		9,650	88	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Medium
HEA9RC4DN-BCG		9,650	88	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Wide
HEA9NC4DN-BCG		9,650	88	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Narrow
Junction Box Models ²										
HEA9MC4PN-JCG		23,500	212	235	110	IP66	110 - 277V AC	5000K (cool white)	Glass	Medium
HEA9RC4PN-JCG		23,500	212	235	110	IP66	110 - 277V AC	5000K (cool white)	Glass	Wide
HEA9NC4PN-JCG		23,500	212	235	110	IP66	110 - 277V AC	5000K (cool white)	Glass	Narrow
HEA9MC4KN-JCG		16,000	144	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Medium
HEA9RC4KN-JCG		16,000	144	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Wide
HEA9NC4KN-JCG		16,000	144	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Narrow
HEA9MC4GN-JCG		12,500	112	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Medium
HEA9RC4GN-JCG		12,500	112	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Wide
HEA9NC4GN-JCG		12,500	112	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Narrow
HEA9MC4DN-JCG		9,650	88	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Medium
HEA9RC4DN-JCG		9,650	88	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Wide
HEA9NC4DN-JCG		9,650	88	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Narrow

All values typical unless otherwise stated, Lumen values are typical (tolerance +/- 10%).

¹For optional glass fragment retention film, change the 11th character from a **C** to a **E**. Example: HEA9MC4PN-**BCG** becomes HEA9MC4PN-**BEG**

²Junction box models come standard with M20 entries. For M25 entries change the 10th character from **J** to **K**. Example: HEA9MC4PN-**JCG** becomes HEA9MC4PN-**KCG**

SafeSite® LED High Bay - High Efficiency - ATEX / IECEx

Ordering Information - Hydrogen Environments

Part Number	Hydrogen Environments	Initial Fixture Lumens	Typical Wattage	Maximum Wattage	Lm/W	IP Rating	Voltage	Colour Temperature (CCT)	Lens	Light Distribution
Hydrogen Environments - Standard Models										
HEH9MC4PN-BCG	•	23,500	212	235	110	IP66	110 - 277V AC	5000K (cool white)	Glass	Medium
HEH9RC4PN-BCG	•	23,500	212	235	110	IP66	110 - 277V AC	5000K (cool white)	Glass	Wide
HEH9NC4PN-BCG	•	23,500	212	235	110	IP66	110 - 277V AC	5000K (cool white)	Glass	Narrow
HEH9MC4KN-BCG	•	16,000	144	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Medium
HEH9RC4KN-BCG	•	16,000	144	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Wide
HEH9NC4KN-BCG	•	16,000	144	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Narrow
HEH9MC4GN-BCG	•	12,500	112	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Medium
HEH9RC4GN-BCG	•	12,500	112	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Wide
HEH9NC4GN-BCG	•	12,500	112	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Narrow
HEH9MC4DN-BCG	•	9,650	88	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Medium
HEH9RC4DN-BCG	•	9,650	88	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Wide
HEH9NC4DN-BCG	•	9,650	88	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Narrow
Hydrogen Environments - Junction Box Models ²										
HEH9MC4PN-JCG	•	23,500	212	235	110	IP66	110 - 277V AC	5000K (cool white)	Glass	Medium
HEH9RC4PN-JCG	•	23,500	212	235	110	IP66	110 - 277V AC	5000K (cool white)	Glass	Wide
HEH9NC4PN-JCG	•	23,500	212	235	110	IP66	110 - 277V AC	5000K (cool white)	Glass	Narrow
HEH9MC4KN-JCG	•	16,000	144	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Medium
HEH9RC4KN-JCG	•	16,000	144	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Wide
HEH9NC4KN-JCG	•	16,000	144	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Narrow
HEH9MC4GN-JCG	•	12,500	112	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Medium
HEH9RC4GN-JCG	•	12,500	112	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Wide
HEH9NC4GN-JCG	•	12,500	112	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Narrow
HEH9MC4DN-JCG	•	9,650	88	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Medium
HEH9RC4DN-JCG	•	9,650	88	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Wide
HEH9NC4DN-JCG	•	9,650	88	235	110	IP66	100 - 277V AC	5000K (cool white)	Glass	Narrow

All values typical unless otherwise stated, Lumen values are typical (tolerance +/- 10%).

¹For optional glass fragment retention film, change the 11th character from a **C** to a **E**. Example: HEA9MC4PN-**BCG** becomes HEA9MC4PN-**BEG**

²Junction box models come standard with M20 entries. For M25 entries change the 10th character from **J** to **K**. Example: HEA9MC4PN-**JCG** becomes HEA9MC4PN-**KCG**

North American HQ

1501 Route 34 South
Farmingdale, NJ 07727
Tel: 732-919-3119
Fax: 732-751-5778
info@dialight.com

EMEA Technical Centre

Ejby Industrivej 91 B
200 Glostrup
Tel: +45 8877 4545 (Denmark)
Tel: +44 1638 666541 (UK)
Tel: +49 89 12089 5713 (Germany)
Tel: +33 3 23 22 62 58 (France)
sales-europe@dialight.com

Houston

16830 Barker Springs Rd
Ste 407
Houston, TX 77084
Tel: 732-919-3119
Faz: 281-492-1531
info@dialight.com

Middle East

Level 42
Emirates Towers (Office Tower)
Sheikh Zayed Road
Dubai, United Arab Emirates
Fax: +971 (0) 4319 7686
Tel: +971 (0) 4319 7686

Australia

38 O'Malley Street
Osborne Park, WA 6017
Tel: +61 (0) 8 9244 7600
Fax: +61 (0) 8 9244 7601
info@dialight.com.au

Southeast Asia

33 Ubi Avenue 3
#07-72 Vertex (Tower A)
Singapore 408868
Tel: +65 6578 7157
Fax: +65 6578 7150
enquiry@dialight.com.sg

Brazil

Alameda Mercurio,
225 – American Park Empresarial NR
Indaiatuba – SP – 13347– 662
Tel: +55 (19) 3113-4300
Fax: +55 (19) 3113-4300
brasil@dialight.com

ALL VALUES ARE DESIGN OR TYPICAL VALUES WHEN MEASURED UNDER LABORATORY CONDITIONS. THE LIGHTING EFFICIENCY STATEMENTS CONTAINED HEREIN ARE CALCULATED ON A LUMEN PER WATTS BASIS WHEN COMPARING FIXTURES WITH SIMILAR FEATURES. ALL INFORMATION PROVIDED IS ACCURATE AS OF THE DATE OF PUBLICATION, IS SUBJECT TO CHANGE WITHOUT NOTICE AND DOES NOT FORM PART OF ANY CONTRACT WITH DIALIGHT. DIALIGHT DOES NOT WARRANT OR REPRESENT THAT ITS PRODUCTS ARE FIT FOR ANY PARTICULAR PURPOSE AND HAS NO RESPONSIBILITY FOR THE [INAPPROPRIATE/UNAUTHORISED/NON-APPROVED] USE OF ANY DIALIGHT PRODUCTS BY THE END USER.

Dialight reserves the right to make changes at any time in order to supply the best product possible.

The most current version of this document will always be available at: www.dialight.com