



# Dialight SafeSite® LED Area Light

## Popular Part Numbers - Americas Region- UL



Legacy Part Number	Part Number	Lumens	Watts	Voltage	CCT & CRI	Lens	Optics	lm/W	Mounting
HZD9C2N	ALD5BC26DNWNGN	5300	40	100-277 VAC, 120-250 VDC	5000K, 80CRI	Polycarbonate - Clear	360°	133	3/4" NPT
HZD5C2GC	ALD7BC26DCNNGN	5700	40	100-277 VAC, 120-250 VDC	5000K, 80CRI	Glass - Clear	360°	143	Crouse-Hinds Retrofit Adapter
HZD5C2G	ALD7BC26DNWNGN	5700	40	100-277 VAC, 120-250 VDC	5000K, 80CRI	Glass - Clear	360°	143	3/4" NPT
HZD9C2GC	ALD7BC26DCNNGN	5700	40	100-277 VAC, 120-250 VDC	5000K, 80CRI	Glass - Clear	360°	143	Crouse-Hinds Retrofit Adapter

All information provided is, to the best of Dialight's knowledge, accurate as of the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. When ordering please refer to [www.dialight.com](http://www.dialight.com) for current versions of all product documentation, which shall always prevail over all other versions.