



Dialight

Dialight SafeSite® LED Area Light

Stock Part Numbers - EMEA Region



Part Number	Lumen	Wattage	lm/W	IP Rating	Voltage	Colour Temperature (CCT)	Lens	Beam Distribution
HZJA9C2N	6,000	58	103	IP66	100-277 VAC	5000K (cool white)	Tempered glass	360°
HZJA8C2N	5,600	58	97	IP66	100-277 VAC	5000K (cool white)	Tempered glass	180°
HZJA5C2N	5,100	47	109	IP66	100-277 VAC	5000K (cool white)	Tempered glass	360°
HZJA4C2N	4,600	47	98	IP66	100-277 VAC	5000K (cool white)	Tempered glass	180°
HZJA3C2N	4,000	38	105	IP66	100-277 VAC	5000K (cool white)	Tempered glass	360°
HZJA2C2N	3,600	38	95	IP66	100-277 VAC	5000K (cool white)	Tempered glass	180°
HZJA1C2N	2,200	22	100	IP66	100-277 VAC	5000K (cool white)	Tempered glass	360°
HZJA0C2N	2,200	22	100	IP66	100-277 VAC	5000K (cool white)	Tempered glass	180°

All values typical unless otherwise stated (tolerance +/- 10%).

Part numbers listed are typically available in stock.

Leaded options available, please consult sales.

All information provided is, to the best of Dialight's knowledge, accurate as of the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. When ordering please refer to www.dialight.com for current versions of all product documentation, which shall always prevail over all other versions.

www.dialight.com

Effective January 1, 2018