



# Dialight DuroSite® LED Floodlight 10/15K

Popular Part Numbers - Americas Region- UL



Part Number	Fixture Lumens	Watt	lm/W	Voltage	Lens	CCT	Beam Distribution
100-277 VAC Models - Glass Lens							
FLW466NC4NG	15,000	135	111	100-277 VAC	Tempered glass	5000K (cool white)	NEMA 6 (115°)
FLW476NC4NG	14,750	135	109	100-277 VAC	Tempered glass	5000K (cool white)	NEMA 7x6 (140° x 115°)
FLW467NC4NG	14,750	135	109	100-277 VAC	Tempered glass	5000K (cool white)	NEMA 6x7 (115° x 140°)
FLW455NC4NG	14,500	140	104	100-277 VAC	Tempered glass	5000K (cool white)	NEMA 5 (93°)
FLW444NC4NG	14,500	140	104	100-277 VAC	Tempered glass	5000K (cool white)	NEMA 4 (52°)
FLW422NC4NG	13,500	140	96	100-277 VAC	Tempered glass	5000K (cool white)	NEMA 2 (23°)
FLW276NC2NG	11,500	106	108	100-277 VAC	Tempered glass	5000K (cool white)	NEMA 7x6 (140° x 115°)
FLW267NC2NG	11,500	106	108	100-277 VAC	Tempered glass	5000K (cool white)	NEMA 6x7 (115° x 140°)
FLW266NC2NG	11,250	106	106	100-277 VAC	Tempered glass	5000K (cool white)	NEMA 6 (115°)
FLW255NC2NG	11,000	106	104	100-277 VAC	Tempered glass	5000K (cool white)	NEMA 5 (93°)
FLW244NC2NG	10,500	106	99	100-277 VAC	Tempered glass	5000K (cool white)	NEMA 4 (52°)
FLW222NC2NG	10,750	106	101	100-277 VAC	Tempered glass	5000K (cool white)	NEMA 2 (23°)

All values typical unless otherwise stated (tolerance +/- 10%).

Part numbers listed in the table above are cool white. For neutral white models, replace the 8th character with an **N**. For bronze powder coat, replace the 10th character with a **Z**.

# Dialight DuroSite® LED Floodlight-10/15K

## Popular Part Numbers - Americas Region- UL

Part Number	Fixture Lumens	Watt	lm/W	Voltage	Lens	CCT	Beam Distribution
<b>100-277 VAC Models - Polycarbonate Lens</b>							
FLW466NC4NP	14,000	135	104	100-277 VAC	Polycarbonate	5000K (cool white)	NEMA 6 (115°)
FLW476NC4NP	13,750	135	102	100-277 VAC	Polycarbonate	5000K (cool white)	NEMA 7x6 (140° x 115°)
FLW467NC4NP	13,750	135	102	100-277 VAC	Polycarbonate	5000K (cool white)	NEMA 6x7 (115° x 140°)
FLW455NC4NP	13,500	140	96	100-277 VAC	Polycarbonate	5000K (cool white)	NEMA 5 (93°)
FLW444NC4NP	13,500	140	96	100-277 VAC	Polycarbonate	5000K (cool white)	NEMA 4 (52°)
FLW422NC4NP	12,500	140	89	100-277 VAC	Polycarbonate	5000K (cool white)	NEMA 2 (23°)
FLW276NC2NP	10,500	106	99	100-277 VAC	Polycarbonate	5000K (cool white)	NEMA 7x6 (140° x 115°)
FLW267NC2NP	10,500	106	99	100-277 VAC	Polycarbonate	5000K (cool white)	NEMA 6x7 (115° x 140°)
FLW266NC2NP	10,250	106	97	100-277 VAC	Polycarbonate	5000K (cool white)	NEMA 6 (115°)
FLW255NC2NP	10,000	106	94	100-277 VAC	Polycarbonate	5000K (cool white)	NEMA 5 (93°)
FLW244NC2NP	9,500	106	89	100-277 VAC	Polycarbonate	5000K (cool white)	NEMA 4 (52°)
FLW222NC2NP	9,750	106	92	100-277 VAC	Polycarbonate	5000K (cool white)	NEMA 2 (23°)
<b>347-480 VAC Models - Glass Lens</b>							
FLW276NC5NG	11,750	112	105	347-480 VAC	Tempered glass	5000K (cool white)	NEMA 7x6 (140° x 115°)
FLW266NC5NG	11,250	112	100	347-480 VAC	Tempered glass	5000K (cool white)	NEMA 6 (115°)
FLW255NC5NG	10,000	112	89	347-480 VAC	Tempered glass	5000K (cool white)	NEMA 5 (93°)
FLW244NC5NG	10,000	112	89	347-480 VAC	Tempered glass	5000K (cool white)	NEMA 4 (52°)
FLW222NC5NG	10,000	112	89	347-480 VAC	Tempered glass	5000K (cool white)	NEMA 2 (23°)

All values typical unless otherwise stated (tolerance +/- 10%).

Part numbers listed in the table above are cool white. For neutral white models, replace the 8th character with an **N**. For bronze powder coat, replace the 10th character with a **Z**.

All information provided is, to the best of Dialight's knowledge, accurate as of the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. When ordering please refer to [www.dialight.com](http://www.dialight.com) for current versions of all product documentation, which shall always prevail over all other versions.