



Dialight SafeSite[®] LED High Bay

Stock Part Numbers - EMEA Region



Part Number	Fixture Lumens	Typical Wattage	Maximum Wattage	lm/W	IP Rating	Voltage	Colour Temperature (CCT)	Lens	Beam Distribution
Junction Box Models									
HEA9MC4PN-KCG	23,500	212	235	110	IP66	110-277 VAC	5000K (cool white)	Glass	Medium
HEA9NC4PN-KCG	23,500	212	235	110	IP66	110-277 VAC	5000K (cool white)	Glass	Narrow
HEA9MC4KN-KCG	16,000	144	235	110	IP66	100-277 VAC	5000K (cool white)	Glass	Medium
HEA9NC4KN-KCG	16,000	144	235	110	IP66	100-277 VAC	5000K (cool white)	Glass	Narrow
HEA9MC4GN-KCG	12,500	112	235	110	IP66	100-277 VAC	5000K (cool white)	Glass	Medium
HEA9NC4GN-KCG	12,500	112	235	110	IP66	100-277 VAC	5000K (cool white)	Glass	Narrow
HEA9MC4DN-KCG	9,650	88	235	110	IP66	100-277 VAC	5000K (cool white)	Glass	Medium
HEA9NC4DN-KCG	9,650	88	235	110	IP66	100-277 VAC	5000K (cool white)	Glass	Narrow

All values typical unless otherwise stated (tolerance +/- 10%).

Part numbers listed are typically available in stock.

For optional glass fragment retention film, change the 11th character from a C to a E.

Junction box models come standard with M25 entries. For M20 cable entries and leaded versions consult sales.

All information provided is, to the best of Dialight's knowledge, accurate as of the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. When ordering please refer to www.dialight.com for current versions of all product documentation, which shall always prevail over all other versions.

www.dialight.com

Effective January 1, 2018