



Dialight Vigilant® LED Low Bay

Stock Part Numbers - EMEA Region



Part Number	Legacy Part Number	Lumens	Watts	lm/W	Voltage	CCT	CRI	Lens	Beam Distribution
Standard Models with 3m Cable & Hook Mount									
LEELUC2CDHWNGN		18,000	154	117	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
LEELUC2BDHWNGN		14,000	114	123	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
LEELUC29DHWNGN		9,000	80	122	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
LEELUC26DHWNGN	LBW1C1DEUH	6,000	56	116	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
LEELUC24DHWNGN	LBW1C5AEUH	4,000	42	101	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
Integrated Wiring Box - comes standard with bracket HBXW3									
LWELUC2CDANNGN		18,000	154	117	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
LWELUC2BDANNGN		14,000	114	123	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
LWELUC29DANNGN		9,750	80	122	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
LWELUC26DANNGN		6,500	56	116	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
LWELUC24DANNGN		4,250	42	101	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide

Notes

Note 1: Models in chart above are 5000K CCT. For 4000K CCT change the 6th character from C to N & deduct 3% from the lumen table.

Note 2: Models with integrated wiring box are upgradeable to DALI & Wireless controls. Consult local Dialight sales office for availability.

Dialight Vigilant® LED Low Bay

Stock Part Numbers - EMEA Region

Part Number	Legacy Part Number	Lumens	Watts	lm/W	Voltage	CCT	CRI	Lens	Beam Distribution
Integrated Wiring Box with Occupancy Sensor									
LWELUC2CMANNGN		18,000	154	117	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
LWELUC2BMANNGN		14,000	114	123	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
LWELUC29MANNGN		9,750	80	122	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
LWELUC26MANNGN		6,500	56	116	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
LWELUC24MANNGN		4,250	42	101	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide

Notes

Note 1: Models in chart above are 5000K CCT. For 4000K CCT change the 6th character from C to N & deduct 3% from the lumen table.

Note 2: Models with integrated wiring box are upgradeable to DALI & Wireless controls. Consult local Dialight sales office for availability.