



Dialight DuroSite® LED Linear- LT/LP

Popular Part Numbers - Americas Region- UL



Low Profile

Part Number	Length	CRI	Fixture Lumens	Watt	lm/W	Voltage	CCT	Lens	Beam Distribution
LPM3C4M2P	4'	75	7,250	66	110	100-277 VAC	5000K (cool white)	Clear polycarbonate	Medium
LPM3C4H2W	4'	75	6,700	66	102	100-277 VAC	5000K (cool white)	Diffused polycarbonate	Medium
LPM3B4M2P	4'	80	6,500	66	98	100-277 VAC	5000K (cool white)	Clear polycarbonate	Medium
LPM3B4H2W	4'	80	6,000	66	91	100-277 VAC	5000K (cool white)	Diffused polycarbonate	Medium
LPM3C4D2P	2'	75	3,600	33	109	100-277 VAC	5000K (cool white)	Clear polycarbonate	Medium
LPM3C4B2W	2'	75	3,300	33	100	100-277 VAC	5000K (cool white)	Diffused polycarbonate	Medium
LPM3B4D2P	2'	80	3,200	33	97	100-277 VAC	5000K (cool white)	Clear polycarbonate	Medium
LPM3B4B2W	2'	80	2,900	33	88	100-277 VAC	5000K (cool white)	Diffused polycarbonate	Medium

All values typical unless otherwise stated (tolerance +/- 10%).

Part numbers listed in the table above are cool white. For neutral white models, replace the 5th character with an **N**.

Dialight DuroSite® LED Linear- LT/LP

Popular Part Numbers - Americas Region- UL



Top Conduit

Part Number	Length	CRI	Fixture Lumens	Watt	lm/W	Voltage	CCT	Lens	Beam Distribution
LTM3C4M2P	4'	75	7,250	66	110	100-277 VAC	5000K (cool white)	Clear polycarbonate	Medium
LTM3C4H2W	4'	75	6,700	66	102	100-277 VAC	5000K (cool white)	Diffused polycarbonate	Medium
LTM3B4M2P	4'	80	6,500	66	98	100-277 VAC	5000K (cool white)	Clear polycarbonate	Medium
LTM3B4H2W	4'	80	6,000	66	91	100-277 VAC	5000K (cool white)	Diffused polycarbonate	Medium
LTM3C4D2P	2'	75	3,600	33	109	100-277 VAC	5000K (cool white)	Clear polycarbonate	Medium
LTM3C4B2W	2'	75	3,300	33	100	100-277 VAC	5000K (cool white)	Diffused polycarbonate	Medium
LTM3B4D2P	2'	80	3,200	33	97	100-277 VAC	5000K (cool white)	Clear polycarbonate	Medium
LTM3B4B2W	2'	80	2,900	33	88	100-277 VAC	5000K (cool white)	Diffused polycarbonate	Medium

All values typical unless otherwise stated (tolerance +/- 10%).

Part numbers listed in the table above are cool white. For neutral white models, replace the 5th character with an **N**.