



# Dialight SafeSite® LED Linear-Battery Backup

## Popular Part Numbers - Americas Region- UL



Classifications: CID2 Groups A, B, C, D • CIID1 E, F, G • CIID2 F, G • CIII

Part Number	Length	CRI	Type	CID1	CID2	CIID1	CIID2	CIII	Voltage	Lens	CCT	Fixture Lumens	Watt	lm/W	Beam Distribution
<b>Class I, Div. 2 Models</b>															
LSD3C4MEP	4'	75	Sustained			•			120-277 VAC	Clear	5000K (cool white)	7,000	85	82	Medium
LSD3C4MNP	4'	75	Maintained			•			120-277 VAC	Clear	5000K (cool white)	7,000	85	82	Medium
<b>Class II Models</b>															
LSF3C4MEP	4'	75	Sustained			•	•	•	120-277 VAC	Clear	5000K (cool white)	7,000	85	82	Medium
LSF3C4MNP	4'	75	Maintained			•	•	•	120-277 VAC	Clear	5000K (cool white)	7,000	85	82	Medium

All values typical unless otherwise stated (tolerance +/- 10%).  
 Part numbers listed in the table above are cool white. For neutral white models, replace the 5th character with an **N**.

All information provided is, to the best of Dialight's knowledge, accurate as of the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. When ordering please refer to [www.dialight.com](http://www.dialight.com) for current versions of all product documentation, which shall always prevail over all other versions.