



# Dialight SafeSite® LED Linear- LT/LP

## Popular Part Numbers - Americas Region- UL



### Low Profile

Part Number	Length	CRI	CID1	CID2	CIID1	CIID2	CIII	Voltage	Lens	CCT	Fixture Lumens	Watt	lm/W	Beam Distribution
<b>Class I, Div. 2 Models</b>														
LPD3C4M2P	4'	75		•				100-277 VAC	Clear	5000K (cool white)	7,250	66	110	Medium
LPD3C4H2W	4'	75		•				100-277 VAC	Diffused	5000K (cool white)	6,700	66	102	Medium
LPD3B4M2P	4'	80		•				100-277 VAC	Clear	5000K (cool white)	6,500	66	98	Medium
LPD3B4H2W	4'	80		•				100-277 VAC	Diffused	5000K (cool white)	6,000	66	91	Medium
LPD3C4D2P	2'	75		•				100-277 VAC	Clear	5000K (cool white)	3,600	33	109	Medium
LPD3C4B2W	2'	75		•				100-277 VAC	Diffused	5000K (cool white)	3,300	33	100	Medium
LPD3B4D2P	2'	80		•				100-277 VAC	Clear	5000K (cool white)	3,200	33	97	Medium
LPD3B4B2W	2'	80		•				100-277 VAC	Diffused	5000K (cool white)	2,900	33	88	Medium
<b>Class II Models</b>														
LPF3C4M2P	4'	75			•	•	•	100-277 VAC	Clear	5000K (cool white)	7,000	66	106	Medium
LPF3C4H2W	4'	75			•	•	•	100-277 VAC	Diffused	5000K (cool white)	6,500	66	98	Medium
LPF3B4M2P	4'	80			•	•	•	100-277 VAC	Clear	5000K (cool white)	6,300	66	95	Medium
LPF3B4H2W	4'	80			•	•	•	100-277 VAC	Diffused	5000K (cool white)	6,000	66	91	Medium
LPF3C4D2P	2'	75			•	•	•	100-277 VAC	Clear	5000K (cool white)	3,500	33	106	Medium
LPF3C4B2W	2'	75			•	•	•	100-277 VAC	Diffused	5000K (cool white)	3,200	33	97	Medium
LPF3B4D2P	2'	80			•	•	•	100-277 VAC	Clear	5000K (cool white)	3,000	33	91	Medium
LPF3B4B2W	2'	80			•	•	•	100-277 VAC	Diffused	5000K (cool white)	2,700	33	82	Medium

All values typical unless otherwise stated (tolerance +/- 10%).

Part numbers listed in the table above are cool white. For neutral white models, replace the 5th character with an **N**.

# Dialight SafeSite® LED Linear- LT/LP

## Popular Part Numbers - Americas Region- UL



### Top Conduit

Classifications: CID2 Groups A, B, C, D • CIID1 E, F, G • CIID2 F, G • CIII

Part Number	Length	CRI	CID1	CID2	CIID1	CIID2	CIII	Voltage	Lens	CCT	Fixture Lumens	Watt	lm/W	Beam Distribution
<b>Class I, Div. 2 Models</b>														
LTD3C4M2P	4'	75		•				100-277 VAC	Clear	5000K (cool white)	7,250	66	110	Medium
LTD3C4H2W	4'	75		•				100-277 VAC	Diffused	5000K (cool white)	6,700	66	102	Medium
LTD3B4M2P	4'	80		•				100-277 VAC	Clear	5000K (cool white)	6,500	66	98	Medium
LTD3B4H2W	4'	80		•				100-277 VAC	Diffused	5000K (cool white)	6,000	66	91	Medium
LTD3C4D2P	2'	75		•				100-277 VAC	Clear	5000K (cool white)	3,600	33	109	Medium
LTD3C4B2W	2'	75		•				100-277 VAC	Diffused	5000K (cool white)	3,300	33	100	Medium
LTD3B4D2P	2'	80		•				100-277 VAC	Clear	5000K (cool white)	3,200	33	97	Medium
LTD3B4B2W	2'	80		•				100-277 VAC	Diffused	5000K (cool white)	2,900	33	88	Medium
<b>Class II Models</b>														
LTF3C4M2P	4'	75			•	•	•	100-277 VAC	Clear	5000K (cool white)	7,000	66	106	Medium
LTF3C4H2W	4'	75			•	•	•	100-277 VAC	Diffused	5000K (cool white)	6,500	66	98	Medium
LTF3B4M2P	4'	80			•	•	•	100-277 VAC	Clear	5000K (cool white)	6,300	66	95	Medium
LTF3B4H2W	4'	80			•	•	•	100-277 VAC	Diffused	5000K (cool white)	6,000	66	91	Medium
LTF3C4D2P	2'	75			•	•	•	100-277 VAC	Clear	5000K (cool white)	3,500	33	106	Medium
LTF3C4B2W	2'	75			•	•	•	100-277 VAC	Diffused	5000K (cool white)	3,200	33	97	Medium
LTF3B4D2P	2'	80			•	•	•	100-277 VAC	Clear	5000K (cool white)	3,000	33	91	Medium
LTF3B4B2W	2'	80			•	•	•	100-277 VAC	Diffused	5000K (cool white)	2,700	33	82	Medium

All values typical unless otherwise stated (tolerance +/- 10%).

Part numbers listed in the table above are cool white. For neutral white models, replace the 5th character with an **N**.