



Dialight DuroSite® LED Linear Stainless Steel

Stock Part Numbers - APAC Region



Australia & Asia Order Codes - CE

Current Part Number	Historic Part Number	Fixture Lumens	Wattage	lm/W	Voltage	Colour Temperature (CCT)	Lens	Beam Distribution
Non-Emergency Models								
EL-1N6M-SSCB4	EL-1C3M-SSCB	2,450	34	70	100-277 VAC	4000K (neutral white)	Polycarbonate	Medium
EL-1N6R-SSCB4	EL-1C3R-SSCB	4,800	67	68	100-277 VAC	4000K (neutral white)	Polycarbonate	Medium
Emergency Models								
ELE-2N7M-SSCB4	ELE-1C3M-SSCB	2,450	35	70	230-240 VAC	4000K (neutral white)	Polycarbonate	Medium
ELE-2N7R-SSCB4	ELE-1C3R-SSCB	4,800	70	68	230-240 VAC	4000K (neutral white)	Polycarbonate	Medium

All values typical unless otherwise stated (tolerance +/- 10%).

Part numbers listed in **bold** are typically available in stock.

Part numbers listed in the table above are neutral white. For cool white models, replace the 4th (non-emergency) or 5th (emergency) character with a **C**.

All information provided is, to the best of Dialight's knowledge, accurate as of the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. When ordering please refer to www.dialight.com for current versions of all product documentation, which shall always prevail over all other versions.