




# Dialight DuroSite® LED Linear- Stainless Steel

Stock Part Numbers - EMEA Region



Part Number	Lumens	Wattage	lm/W	IP Rating	Voltage	Colour Temperature (CCT)	Lens	Beam Distribution
<b>Standard Model- 100-277 VAC</b>								
EL-1C6R-SSCB4	5,100	67	76	IP66/67	100-277 VAC	5000K (cool white)	Polycarbonate	Medium
EL-1C6M-SSCB4	2,600	34	76	IP66/67	100-277 VAC	5000K (cool white)	Polycarbonate	Medium
<b>Standard Model- 230-240 VAC</b>								
ELE-2C7R-SSCB4	5,100	70	73	IP66/67	230-240 VAC	5000K (cool white)	Polycarbonate	Medium
ELE-2C7M-SSCB4	2,600	35	74	IP66/67	230-240 VAC	5000K (cool white)	Polycarbonate	Medium

All values typical unless otherwise stated (tolerance +/- 10%). Part numbers listed are typically available in stock. M20 cable entry options available, please consult local Dialight sales office. Neutral white options available, please consult local Dialight sales office.

All information provided is, to the best of Dialight's knowledge, accurate as of the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. When ordering please refer to [www.dialight.com](http://www.dialight.com) for current versions of all product documentation, which shall always prevail over all other versions.