



Dialight SafeSite® LED Linear-Stainless Steel

Stock Part Numbers - EMEA Region



Part Number	Fixture Lumens	Emergency Mode Lumens	Wattage	lm/W	Voltage	Colour Temperature (CCT)	Lens	Beam Distribution
Standard Models								
ELA-1C6R-SSCB4	5,100		67	76	110-250 VAC	5000K (cool white)	Polycarbonate	Medium
ELA-1C6M-SSCB4	2,600		34	76	110-250 VAC	5000K (cool white)	Polycarbonate	Medium
ELA-1N6R-SSCB4	4,850		67	72	110-250 VAC	4000K (neutral white)	Polycarbonate	Medium
ELA-1N6M-SSCB4	2,500		34	74	110-250 VAC	4000K (neutral white)	Polycarbonate	Medium
Shower Safe Models								
ELA-1G3M-SSC			34		110-250 VAC	Green	Polycarbonate	Medium
Emergency Models								
ELEA-2C7R-SSCB4	5,100	271	70	73	230 / 240 VAC	5000K (cool white)	Polycarbonate	Medium
ELEA-2C7M-SSCB4	2,600	271	35	74	230 / 240 VAC	5000K (cool white)	Polycarbonate	Medium

All values typical unless otherwise stated (tolerance +/- 10%).
M20 options available, please consult local Dialight sales office for availability.

All information provided is, to the best of Dialight's knowledge, accurate as of the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. When ordering please refer to www.dialight.com for current versions of all product documentation, which shall always prevail over all other versions.