



Dialight StreetSense® LED Street Light

Stock Part Numbers - APAC Region



Australia & Asia Order Codes- CE/UL

| Part Number | Fixture Lumens | Wattage | lm/W | Voltage | Colour Temperature (CCT) | Lens | Light Engines |
|----------------------------|----------------|---------|------|-------------|--------------------------|----------------|---------------|
| Standard Models - Type III | | | | | | | |
| SL3N5CLGGEU | 5,500 | 65 | 85 | 100-277 VAC | 4300K (neutral white) | Tempered glass | 1 |
| SL3N5DLGGEU | 6,750 | 83 | 81 | 100-277 VAC | 4300K (neutral white) | Tempered glass | 1 |
| SL3N5HLGGEU | 10,900 | 131 | 83 | 100-277 VAC | 4300K (neutral white) | Tempered glass | 2 |
| SL3N5ILGGEU | 13,250 | 165 | 80 | 100-277 VAC | 4300K (neutral white) | Tempered glass | 2 |
| SL3N5RLGGEU | 16,000 | 190 | 84 | 100-277 VAC | 4300K (neutral white) | Tempered glass | 3 |
| SL3N5SLGGEU | 20,250 | 252 | 80 | 100-277 VAC | 4300K (neutral white) | Tempered glass | 3 |

All values typical unless otherwise stated (tolerance +/- 10%).

Part numbers listed in **bold** are typically available in stock.

Part numbers listed in the table above are neutral white. For cool white models, replace the 6th character with a **C**.

All information provided is, to the best of Dialight's knowledge, accurate as of the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. When ordering please refer to www.dialight.com for current versions of all product documentation, which shall always prevail over all other versions.