

# AUTHORIZATION TO MARK

This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report. This authorization also applies to multiple listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The certification mark(s) may be applied only at the location of the Party Authorized To Apply Mark.

<b>Applicant:</b> Dialight Corporation  <b>Address:</b> 1501 Route 34 South Farmingdale, NJ 08005 USA  <b>Country:</b> USA <b>Contact:</b> David Weimer <b>Phone:</b> (732) 919-3119 <b>FAX:</b> (732) 223-4832 <b>Email:</b> dweimer@dialight.com	<b>Manufacturer:</b> <b>Dialight Corporation</b>  <b>Address:</b> Calle Lirios S/N, Col. Carlos Pacheco Ensenada, B.C. Mexico 22830  <b>Country:</b> Mexico <b>Contact:</b> Angel Escamilla <b>Phone:</b> 52-646-156-7080 <b>FAX:</b> NA <b>Email:</b> Aescamilla@dailight.com
---	---

**Party Authorized To Apply Mark:** Same as Manufacturer  
**Report Issuing Office:** Cortland, NY



**Control Number:** 3081714      **Authorized by:** \_\_\_\_\_  
for Thomas J. Patterson, Certification Manager



This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Intertek Testing Services NA Inc.  
 545 East Algonquin Road, Arlington Heights, IL 60005  
 Telephone 800-345-3851 or 847-439-5667 Fax 312-283-1672

<b>Standard(s):</b>	UL Standard for Safety Luminaires for Use in Hazardous (Classified) Locations; UL 844; 12th Ed; January 11, 2006; Revised November 20, 2008  Electric Luminaires for Use in Hazardous Locations; CSA C22.2 No. 137-M1981; General Instruction No. 3; November 1982; Reaffirmed 1993  Nonincendive Electrical Equipment for Use in Class I and II, Division 2 and Class III, Divisions 1 and 2 Hazardous (Classified) Locations; ANSI/ISA-12.12.01-2012, July 09, 2012  Non-Incedive Electrical Equipment for Use in Class I, Division 2 Hazardous Locations; CSA C22.2 No. 213-M1987; General Instruction No. 1 March 1987; Reaffirmed 2013
<b>Product:</b>	LED Luminaire
<b>Brand Name:</b>	Wallpack / Bulk-Head



# AUTHORIZATION TO MARK

	Product Family	Optic	LED Colour	Voltage	Initial Lumens	Bracket	Finish	Glazing Glass	Gland Location	Thread Options	Option
<b>Models:</b>	WPC NOTE:WPC for non emergency fixtures	X	X	3	X	X	XX	X	X	X	XX
	WEC NOTE "WEC for use with emergency driver"	2= wide	N= Neutral	3=100 to 277Vac	C= (9 leds)	N= None	any color	C=Clear	Blank= 2 on 1 side	Blank=2 M20	
		3= flood	C= Cool White W= warm white	4= 230/240Vac	H= (18 leds)	F= Flush		F=Frosted	R= Rear	3=M20	
		4=oval 35x55 deg		5= 110/120Vac	L= (27 leds)	A= Angle			E= 2+1 on ends T=1 on each end plus rear	4=M25	
		5=oval 55x35deg	A= Amber							5=NPT3/4 6=NPT 1.0 only works with "T" gland option	
		6= linear blended	R= Red						H= 2+1+Rear		
	7= oval full	G= Green									
	0= no optic	B= Blue									

# AUTHORIZATION TO MARK

This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report. This authorization also applies to multiple listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The certification mark(s) may be applied only at the location of the Party Authorized To Apply Mark.

<b>Applicant:</b>	Dialight Corporation	<b>Manufacturer:</b>	<b>Dialight Europe LTD</b>
<b>Address:</b>	1501 Route 34 South Farmingdale, NJ 08005 USA	<b>Address:</b>	Exning Road, Newmarket Suffolk, UK CB80AX
<b>Country:</b>	USA	<b>Country:</b>	UK
<b>Contact:</b>	David Weimer	<b>Contact:</b>	QC Department
<b>Phone:</b>	(732) 919-3119	<b>Phone:</b>	4.40116E+13
<b>FAX:</b>	(732) 223-4832	<b>FAX:</b>	NA
<b>Email:</b>	dweimer@dialight.com	<b>Email:</b>	frank.trott@dialight.co.uk

**Party Authorized To Apply Mark:** Same as Manufacturer  
**Report Issuing Office:** Cortland, NY



**Control Number:** 4001646      **Authorized by:** \_\_\_\_\_  
 for Thomas J. Patterson, Certification Manager



This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Intertek Testing Services NA Inc.  
 545 East Algonquin Road, Arlington Heights, IL 60005  
 Telephone 800-345-3851 or 847-439-5667 Fax 312-283-1672

<b>Standard(s):</b>	UL Standard for Safety Luminaires for Use in Hazardous (Classified) Locations; UL 844; 12th Ed; January 11, 2006; Revised November 20, 2008
	Electric Luminaires for Use in Hazardous Locations; CSA C22.2 No. 137-M1981; General Instruction No. 3; November 1982; Reaffirmed 1993
	Nonincendive Electrical Equipment for Use in Class I and II, Division 2 and Class III, Divisions 1 and 2 Hazardous (Classified) Locations; ANSI/ISA-12.12.01-2012, July 09, 2012
<b>Product:</b>	LED Luminaire
<b>Brand Name:</b>	Wallpack / Bulk-Head



# AUTHORIZATION TO MARK

	Product Family	Optic	LED Colour	Voltage	Initial Lumens	Bracket	Finish	Glazing Glass	Gland Location	Thread Options	Option
<b>Models:</b>	WPC NOTE:WPC for non emergency fixtures	X	X	3	X	X	XX	X	X	X	XX
	WEC NOTE "WEC for use with emergency driver"	2= wide	N= Neutral	3=100 to 277Vac	C= (9 leds)	N= None	any color	C=Clear	Blank= 2 on 1 side	Blank=2 M20	
	3= flood	C= Cool White W= warm white	4= 230/240Vac	H= (18 leds)	F= Flush		F=Frosted	R= Rear	3=M20		
	4=oval 35x55 deg		5= 110/120Vac	L= (27 leds)	A= Angle		E= 2+1 on ends T=1 on each end plus rear	4=M25			
	5=oval 55x35deg	A= Amber						5=NPT3/4 6=NPT 1.0 only works with "T" gland option			
	6= linear blended	R= Red					H= 2+1+Rear				
	7= oval full	G= Green									
0= no optic	B= Blue										

# AUTHORIZATION TO MARK

This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report. This authorization also applies to multiple listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The certification mark(s) may be applied only at the location of the Party Authorized To Apply Mark.

<b>Applicant:</b>	Dialight Corporation	<b>Manufacturer:</b>	<b>Dialight Corporation</b>
<b>Address:</b>	1501 Route 34 South Farmingdale, NJ 08005 USA	<b>Address:</b>	315 Industrial Drive Roxboro, North Carolina, 27573-6181
<b>Country:</b>	USA	<b>Country:</b>	USA
<b>Contact:</b>	David Weimer	<b>Contact:</b>	Rudy Lopez
<b>Phone:</b>	(732) 919-3119	<b>Phone:</b>	(336) 597-2291
<b>FAX:</b>	(732) 223-4832	<b>FAX:</b>	NA
<b>Email:</b>	dweimer@dialight.com	<b>Email:</b>	rlopez@dialight.com

**Party Authorized To Apply Mark:** Same as Manufacturer  
**Report Issuing Office:** Cortland, NY



**Control Number:** 4001632      **Authorized by:** \_\_\_\_\_  
 for Thomas J. Patterson, Certification Manager



This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Intertek Testing Services NA Inc.  
 545 East Algonquin Road, Arlington Heights, IL 60005  
 Telephone 800-345-3851 or 847-439-5667 Fax 312-283-1672

<b>Standard(s):</b>	UL Standard for Safety Luminaires for Use in Hazardous (Classified) Locations; UL 844; 12th Ed; January 11, 2006; Revised November 20, 2008
	Electric Luminaires for Use in Hazardous Locations; CSA C22.2 No. 137-M1981; General Instruction No. 3; November 1982; Reaffirmed 1993
	Nonincendive Electrical Equipment for Use in Class I and II, Division 2 and Class III, Divisions 1 and 2 Hazardous (Classified) Locations; ANSI/ISA-12.12.01-2012, July 09, 2012
<b>Product:</b>	LED Luminaire
<b>Brand Name:</b>	Wallpack / Bulk-Head



# AUTHORIZATION TO MARK

	Product Family	Optic	LED Colour	Voltage	Initial Lumens	Bracket	Finish	Glazing Glass	Gland Location	Thread Options	Option
<b>Models:</b>	WPC NOTE:WPC for non emergency fixtures	X	X	3	X	X	XX	X	X	X	XX
	WEC NOTE "WEC for use with emergency driver"	2= wide	N= Neutral	3=100 to 277Vac	C= (9 leds)	N= None	any color	C=Clear	Blank= 2 on 1 side	Blank=2 M20	
		3= flood	C= Cool White W= warm white	4= 230/240Vac	H= (18 leds)	F= Flush		F=Frosted	R= Rear	3=M20	
		4=oval 35x55 deg		5= 110/120Vac	L= (27 leds)	A= Angle			E= 2+1 on ends T=1 on each end plus rear	4=M25	
		5=oval 55x35deg	A= Amber							5=NPT3/4 6=NPT 1.0 only works with "T" gland option	
		6= linear blended	R= Red						H= 2+1+Rear		
		7= oval full	G= Green								
	0= no optic	B= Blue									