



The Dialight® Reliant™ LED High Bay

Now available in EMEA & APAC

MAY 2019

THE RUGGED AND EFFICIENT PERFORMANCE YOU TRUST, NOW FOR LIGHT INDUSTRIAL APPLICATIONS.

Designed for superior energy efficiency and value in warehouses, light manufacturing and other large indoor spaces. Built with the same uncompromising standards for reliability found in over 1 million Dialight High Bays already in place around the world, Reliant is backed by Dialight's signature 10-year warranty, among the industry's longest, best-in-class protections.

FEATURES & BENEFITS

- CE / ENEC / RCM* certified
- Up to 160 lm/W
- 10 year warranty
- -40°C to +55°C ambient temperature
- 11,000-36,000 lumens
- IP66 rated options
- All units controls enabled

*Values based on preliminary data awaiting validation or certification.



All units are controls enabled and offer DALI 1.0/2.0 standard. Design allows for smart sensor installation at the center

IP66 rated

Multiple optical patterns and lens options available

Replacement parts offered including lenses and surge protection

Easy to install with single-point mounting

Tool-less polymeric wiring box

Rugged aluminum base

Exclusive in-house designed power supply and thermal management system for optimal reliability & longevity

EMEA

EMEA Technical Centre

Ejby Industrivej 91 B
2600 Glostrup
Tel: +45 8877 4545 (Denmark)
Tel: +44 1638 666541 (UK)
Tel: +49 89 12089 5713 (Germany)
Tel: +33 3 23 22 62 58 (France)
sales-europe@dialight.com

Middle East

205, Clover Bay Tower,
Al Abraj Street, Business Bay
P.O. Box 123997 Dubai, U.A.E.
Tel: +971 (4) 818 31 56

APAC

Australia

108 Howe Street
Osborne Park, WA 6017
Tel: +61 (0) 8 9244 7600
Fax: +61 (0) 8 9244 7601
info@dialight.com.au

Southeast Asia

33 Ubi Avenue 3
#07-72 Vertex (Tower A)
Singapore 408868
Tel: +65 6578 7157
Fax: +65 6578 7150
enquiry@dialight.com.sg

DISCLAIMER: *The use of this product without proper installation and inspections, including secondary safety retention/securing, could cause severe injury or death. Dialight products are intended for ultimate purchase, installation and operation by knowledgeable persons trained in the functional assessment, installation, use and maintenance of such products and all customers (including but not limited to end customers) are responsible for assessing the suitability of Dialight products for any given installation requirement. All values and performance data herein are design or typical values when measured under laboratory conditions. Whilst Dialight has used all reasonable endeavours to ensure the completeness and accuracy of information herein, this document does not form part of any contract with Dialight and Dialight does not assume any liability for damages resulting from use of this information or for any third party representations made in relation to Dialight products. The information herein is subject to change without notice. The products / software detailed herein are subject to applicable warranties and terms and conditions of use/purchase. Unless agreed otherwise in writing by an authorised representative of Dialight, Dialight does not represent that its products are fit for a particular purpose and accepts no liability for the installation and/or unauthorised use of its products. When ordering please refer to www.dialight.com for current versions of: (a) relevant product documentation (including the most up to date product data sheets); (b) Dialight terms and conditions of sale; and, (c) Dialight warranty terms. All information provided is, to Dialight's knowledge, accurate at the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. In the event of any discrepancy between this document and information provided on our website, the latter shall prevail.*