

Dialight® LED GRP Linear EMEA & APAC

www.dialight.com



DIALIGHT'S HIGH PERFORMANCE LINEAR FOR HARSH AND HAZARDOUS APPLICATIONS

Dialight's Glass Reinforced Polyester (GRP) linear includes IECEx / ATEX certification for the ultimate solution in heavy industrial and hazardous applications including upstream and downstream oil and gas, petrochemical, mining and heavy manufacturing applications.



- CE certified
- 10 year warranty
- ATEX/IECEx certified for Zone 1, 2, 21 and 22
- Up to 2,875 & 5,750 (nominal) lumen outputs
- IP66/67 rated options
- -40°C to +65°C ambient temperature, emergency models: -20°C to +50°C
- DALI 1.0/2.0 as standard
- Available in 764mm and 1244mm lengths

2





All units are DALI 1.0/2.0 enabled

Textured polycarbonate and textured glass lens options (textured polycarbonate lens as standard)

Rugged, corrosion-resistant housing

Stainless steel safety retention points

www.dialight.com 3

EMEA

Dialight Europe Ltd

Leaf C, Level 36, Tower 42 25 Old Broad Street London, EC2N 1HQ, United Kingdom Tel: +44 (0) 203 058 3540 Customer Service: +44 (0) 163 866 6541 sales-emea@dialight.com

Middle East

205, Clover Bay Tower, Al Abraj Street, Business Bay P.O. Box 123997 Dubai, U.A.E. Tel: +971 (4) 818 31 56

APAC

Australia

108 Howe Street Osborne Park, WA 6017 Tel: +61 (0) 8 9244 7600 Fax: +61 (0) 8 9244 7601 info@dialight.com.au

Southeast Asia

33 Ubi Avenue 3 #07-72 Vertex (Tower A) Singapore 408868 Tel: +65 6578 7157 Fax: +65 6578 7150

enquiry@dialight.com.sg

WARNING / DISCLAIMERS:
Installation & secondary retention. The use of this product without proper installation (including secondary retention / netting) and periodic inspections, could cause severe injury or death. Dialight recommends that all installations should use secondary retention / netting (appropriate to the installation environment) as applicable. Dialight products are intended for ultimate purchase, installation and operation by knowledgeable persons trained in the functional assessment, installation, use and maintenance of such products are intended for ultimate purchase, installation are responsible for assessing the suitability of Dialight products for any given installation requirement. It is the exclusive responsibility of the contractor, installer and/or end-user to: (a) determine the suitability of the product for its intended application; and, (b) ensure that the product is safely installed (with secondary retention / netting as appropriate) and in compliance with all applicable laws and regulations.

Product specifications & warranties. All product information provided is, to the best of Dialight's knowledge, accurate as of the date of publication. All values and performance data herein are design or typical values when measured under laboratory conditions. The information herein is subject to change without notice. The products / software detailed herein are subject to applicable warranties and terms and conditions of use/purchase. Unless agreed otherwise in writing by an authorized representative of Dialight, Dialight does not represent that its products are fit for any particular purpose and accepts no liability for the installation and/or unauthorised use of its products. When ordering, refer to www.dialight.com for current versions of (a) relevant product data sheets); (b) Dialight terms and conditions of sale; and, (c) the relevant product warranties. To the extent that any contract is deemed formed between Dialight and the purchaser of Dialight products and/or an end-user, versions of