

.....Dialight



DuroSite® LED Floodlight - CE
for Indoor and Outdoor Industrial Applications

CE



Features & Benefits

- 10 year warranty
- L70 rated for >100,000 hours @ 25°C ambient
- Instant on/off operation
- Universal input (100-277 VAC), 50/60Hz
- Superior colour rendition index compared to HPS, LPS, MV
- Mercury free
- Resistant to shock and vibration
- Temperature compensation technology for longer life
- Isolated wiring compartment
- Integral Safety Straps


Application

The DuroSite LED Floodlight represents the future of energy efficient facility illumination for industrial applications worldwide. The lighting fixture consumes at least 50% less energy than traditional HID light sources, while reducing maintenance and carbon emissions. This light incorporates both cutting edge LED technology along with proprietary optics to achieve floodlighting comparable with other traditional light sources.

DuroSite® LED Floodlight - CE Standard Model



Patent Pending



Dimensions in mm (inches)

Certifications & Ratings

- CE
- EN55015
- EN61547
- EN60598-1
- EN61000-3-2
- EN62031
- EN62471
- IP66/67 to EN60529
- IK07

Mechanical Information:

Fixture weight:	13.6 kg (30 lb)
Shipping weight:	15.4 kg (34 lb)
Mounting:	Trunnion mounting bracket included
Entry:	(2) M20 cable entries

Electrical Specifications:

Operating Voltage:	100-277 VAC, 50/60Hz
Total system power consumption:	See table
Operating Temp:	-40°C to +65°C (-40°F to +149°F)
Harmonics:	IEC 61000-3-2
Noise Requirements/ EMC:	EN 55015 - conducted and radiated EN 61000-3-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-11

Transient protection:	EN61000-4-5 Verified up to 6kV/20ohms at an independent test laboratory Protection devices capable of 20kV
------------------------------	--

THD:	< 20%
Power Factor:	> 0.9

Construction:

Housing:	Copper-free aluminium
Bracket:	304 Stainless Steel
Finish:	Superior dual coat finish - Sealed polyester topcoat - Chemical-resistant epoxy prime
Lens:	Tempered glass

Photometric Information:

CRI:	80
CCT:	4000K (neutral white)
Field Angles:	Asymmetrical (140° x 115°) Asymmetrical (115° x 140°) Very wide (115°) Wide (93°) Medium (52°) Narrow (23°)
IES Files:	Available at www.dialight.com

All values typical unless otherwise stated (tolerance +/- 10%)

WARNING - INSTALLATION & SECONDARY RETENTION. Use of any Dialight products without proper installation (including secondary retention / netting) and periodic inspections could cause severe injury or death. Dialight recommends that all installations should use secondary retention / netting (appropriate to the installation environment) where applicable. It is the exclusive responsibility of the contractor, installer and/or end-user to: (a) determine the suitability of the product for its intended application; and, (b) ensure that the product is safely installed (with secondary retention / netting where appropriate) and in compliance with all applicable laws and regulations. To the extent permissible under applicable laws, Dialight disclaims all liability for personal injury and/or other damage resulting from any dislodgment or other dislocation of its products.

DuroSite® LED Floodlight - CE Mounting Accessories




Product shipped with bracket installed
(Bracket has locking positions at 0°, (±) 22.5°, (±) 45°, (±) 67.5°, and 90°)



HZXSAFECBLS

- Safety cable kit
- Kit includes: (2) safety cables

Factory Installed Mounting Bracket



WARNING - INSTALLATION & SECONDARY RETENTION. Use of any Dialight products without proper installation (including secondary retention / netting) and periodic inspections could cause severe injury or death. Dialight recommends that all installations should use secondary retention / netting (appropriate to the installation environment) where applicable. It is the exclusive responsibility of the contractor, installer and/or end-user to: (a) determine the suitability of the product for its intended application; and, (b) ensure that the product is safely installed (with secondary retention / netting where appropriate) and in compliance with all applicable laws and regulations. To the extent permissible under applicable laws, Dialight disclaims all liability for personal injury and/or other damage resulting from any dislodgment or other dislocation of its products.

DuroSite® LED Floodlight - CE


Ordering Information & Beam Distribution

Part Number	Fixture Lumens	Wattage	lm/W	Voltage	Colour Temperature (CCT)	Lens	Beam Distribution
FLE466MN4NG	14,250	135	105	100-277 VAC	4000K (neutral white)	Tempered Glass	Very Wide (115°)
FLE476MN4NG	14,000	135	104	100-277 VAC	4000K (neutral white)	Tempered Glass	Asymmetrical (140° x 115°)
FLE467MN4NG	14,000	135	104	100-277 VAC	4000K (neutral white)	Tempered Glass	Asymmetrical (115° x 140°)
FLE455MN4NG	13,750	140	98	100-277 VAC	4000K (neutral white)	Tempered Glass	Wide (93°)
FLE444MN4NG	13,750	140	98	100-277 VAC	4000K (neutral white)	Tempered Glass	Medium (52°)
FLE422MN4NG	12,750	140	91	100-277 VAC	4000K (neutral white)	Tempered Glass	Narrow (23°)
FLE276MN2NG	11,000	109	101	100-277 VAC	4000K (neutral white)	Tempered Glass	Asymmetrical (140° x 115°)
FLE267MN2NG	11,000	109	101	100-277 VAC	4000K (neutral white)	Tempered Glass	Asymmetrical (115° x 140°)
FLE266MN2NG	10,750	109	99	100-277 VAC	4000K (neutral white)	Tempered Glass	Very Wide (115°)
FLE255MN2NG	10,500	109	96	100-277 VAC	4000K (neutral white)	Tempered Glass	Wide (93°)
FLE244MN2NG	10,000	109	92	100-277 VAC	4000K (neutral white)	Tempered Glass	Medium (52°)
FLE222MN2NG	10,250	109	94	100-277 VAC	4000K (neutral white)	Tempered Glass	Narrow (23°)


All values typical unless otherwise stated (tolerance +/- 10%).

Part numbers listed in the table above are powder coated gray. For bronze powder, coat replace the 10th character with **Z**. FLE244MN2NG becomes FLE244MN2ZG.


Beam Distribution




Field angle = 140° x 115°




Field angle = 115° x 140°




Field angle = 115°



Field angle = 93°



Field angle = 52°



Field angle = 23°

DISCLAIMER. All product information provided is, to the best of Dialight's knowledge, accurate as of the date of publication. When ordering, refer to www.dialight.com for current versions of: (a) relevant product documentation (including the relevant product data sheets); (b) Dialight terms and conditions of sale; and, (c) the relevant product warranty. To the extent that any contract is deemed formed between Dialight and the purchaser of Dialight products and/or an end-user, versions of documents available at www.dialight.com as at the date of sale shall be the versions incorporated therein. In the event of any discrepancy between this document or information provided at www.dialight.com, the latter shall prevail.

Australia

38 O'Malley Street
Osborne Park, WA 6017
Tel: +61 (0) 8 9244 7600
Fax: +61 (0) 8 9244 7601
info@dialight.com.au

Southeast Asia

33 Ubi Avenue 3
#07-72 Vertex (Tower A)
Singapore 408868
Tel: +65 6578 7157
Fax: +65 6578 7150
enquiry@dialight.com.sg

WARNING / DISCLAIMERS:

Installation & secondary retention. The use of this product without proper installation (including secondary retention / netting) and periodic inspections, could cause severe injury or death. Dialight recommends that all installations should use secondary retention / netting (appropriate to the installation environment) as applicable. Dialight products are intended for ultimate purchase, installation and operation by knowledgeable persons trained in the functional assessment, installation, use and maintenance of such products and all customers (including but not limited to end customers) are responsible for assessing the suitability of Dialight products for any given installation requirement. It is the exclusive responsibility of the contractor, installer and/or end-user to: (a) determine the suitability of the product for its intended application; and, (b) ensure that the product is safely installed (with secondary retention / netting as appropriate) and in compliance with all applicable laws and regulations.

Product specifications & warranties. All product information provided is, to the best of Dialight's knowledge, accurate as of the date of publication. All values and performance data herein are design or typical values when measured under laboratory conditions. The information herein is subject to change without notice. The products / software detailed herein are subject to applicable warranties and terms and conditions of use/purchase. Unless agreed otherwise in writing by an authorized representative of Dialight, Dialight does not represent that its products are fit for any particular purpose and accepts no liability for the installation and/or unauthorised use of its products. When ordering, refer to www.dialight.com for current versions of: (a) relevant product documentation (including relevant product data sheets); (b) Dialight terms and conditions of sale; and, (c) the relevant product warranties. To the extent that any contract is deemed formed between Dialight and the purchaser of Dialight products and/or an end-user, versions of documents available at www.dialight.com as at the date of sale shall be the versions incorporated therein. In the event of any discrepancy between this document and information provided at www.dialight.com, the latter shall prevail.

Exclusion of liability. To the extent permissible under the relevant law, Dialight disclaims all liability for personal injury and/or other damage resulting from any dislodgment or other dislocation of its products. Whilst Dialight has used its reasonable endeavours to ensure the completeness and accuracy of information herein, Dialight does not assume any liability for damages resulting from use of this information or for any third-party representations made in relation to Dialight products.