

INTRODUCING THE **LED AREA LIGHT**



Dialight's LED Area Light delivers class-leading energy efficiency, functionality and dependability for superior performance in a wide range of applications in the most demanding environments. Designed around Dialight's exclusive purpose-built power supply for long lasting reliability.

The Dialight Area Lighting provides low maintenance fixtures you can count on with unmatched visual clarity for maximum savings and safety. Dialight offers both non-hazardous and hazardous area lights.

FEATURES & BENEFITS

UL 1598/A, UL 844 (CID1, CID2, CIID1, CIID2, CII, CIII), CSA, NOM, UL 924,

CE, ENEC, RCM, IECEx/ATEX (Zone 1, 21)

IP66/67/69, NEMA 4X, IK07 (glass lens)/IK10 (PC lens)

Cool White 5000K, Neutral White 4000K, Warm White 2700K

100-277 VAC, 120-250 VDC, 347-480 VAC, 50/60Hz

Diffused Polycarbonate, Clear Tempered Glass,

Operating temperature range of -40°F + 149°F (-40°C to +65°C)

Up to 9,000 lumens (11,000 & 13,000 lumens coming soon)

Beam Distribution of 360°, 180°, Wide

DLC Premium (available on most models)

Mounting heights up to 30 feet (9m)

Up to 143 lm/W

10 year warranty (most models)

CLICK OR SCAN
TO EXPLORE
DIALIGHT LED AREA
LIGHT ACCESSORIES

