

INDUSTRIAL LED LIGHTING

For General Manufacturing HOT SHEET



Vigilant® High Output High Bay -Low Profile

For non-hazardous high ceiling high bay applications typically 40 feet or above



SafeSite® and Vigilant® Area Lights

For hazardous and non-hazardous lower ceiling indoor or outdoor process and stanchion mount applications*



SafeSite® and Vigilant® High Bay
For non-hazardous and hazardous indoor or outdoor
high bay applications over 14 feet



SafeSite® and Vigilant® Low Bays

For hazardous and non-hazardous lower ceiling indoor or outdoor applications where wider light distribution is critical



ProSite Streetlight
For plant maintained roadways a

For plant maintained roadways and general outdoor



ProSite Floodlight F1 Model
For non-hazardous and hazardous indoor or
outdoor flood lighting applications; multiple beam
patterns available



Reliant™ High Bay
For indoor, light industrial applications and lighter-duty areas of heavy industrial facilities, such as warehouses



SafeSite® and Vigilant®LP/TC Linears

For hazardous and non-hazardous indoor or outdoor fluorescent strip/vaportite replacements, task or inspection lighting, electrical rooms, shops, and process areas. 4ft and 2ft versions available



ProSite Floodlight F2 Model
For non-hazardous indoor or outdoor high power
flood applications (Typical 1,000 watt or better HID
replacement)



