



INDUSTRIAL LED LIGHTING

Wood, Pulp and Paper **HOT SHEET**

Dialight

1 Vigilant® High Output High Bay - Low Profile

For non-hazardous high ceiling high bay applications typically 40 feet or above



9 ProSite Floodlight F2 Model

For non-hazardous indoor or outdoor high power flood applications (Typical 1,000 watt or better HID replacement)



8 SafeSite® and Vigilant® LP/TC Linears

For hazardous and non-hazardous indoor or outdoor fluorescent strip/vaportite replacements, task or inspection lighting, electrical rooms, shops, and process areas. 4ft and 2ft versions available



2 SafeSite® and Vigilant® Area Lights

For hazardous and non-hazardous lower ceiling indoor or outdoor process and stanchion mount applications*



3 Vigilant® High Bay

For non-hazardous indoor or outdoor high bay applications over 14 feet



4 SafeSite® and Vigilant® Low Bays

For hazardous and non-hazardous lower ceiling indoor or outdoor applications where wider light distribution is critical



5 ProSite Streetlight

For plant maintained roadways and general outdoor illumination



6 ProSite Floodlight

For non-hazardous and hazardous indoor or outdoor flood lighting applications; multiple beam patterns available



7 Reliant™ High Bay

For indoor, light industrial applications and lighter-duty areas of heavy industrial facilities, such as warehouses



*Ask about our retrofit adapters to save labor by retrofitting to existing HID infrastructure

www.dialight.com